

Low Profile Lift Table HY 1000 Kg

- ▲ Heavy duty design with larger platform
- ▲ These tables achieve a low closed height, eliminating the need for a pit installation.
- ▲ They are manufactured to all European safety standards including EN1570:1999.
- ▲ Remote power pack with pedestal and controls, protected to IP54.
- ▲ Upper platform fitted with safety perimeter to prevent descent on contact with obstructions.
- ▲ 24V control box with UP and DOWN buttons and emergency stop.
- ▲ External power pack equipped with a relief valve against overloading and a compensated flow valve for controlling lowering speed. Power supply are AC 380V/50HZ/3phase.
- ▲ Hose burst safety valve to stop the lift table lowering in case of hose breakage.
- ▲ Removable lifting eyes to facilitate handling and installation of the lift table.
- ▲ Oilless bushings on pivot points.
- ▲ Loading ramp is a standard equipment.



รายละเอียดผลิตภัณฑ์อาจมีการเปลี่ยนแปลงโดยมิได้แจ้งให้ทราบล่วงหน้า

TECHNICAL DATA		MODEL				
		HY 1001	HY 1002	HY 1003	HY 1004	HY 1005
Capacity	kg	1000				
Platform Width	mm	1140	1140	800	800	1000
Platform Length	mm	1450	1600	1450	1600	1600
Hydraulic Cylinder	set	2				
Lifting Height	mm	860				
Lowering Height	mm	85				
Stroke	mm	775				
Lift Time	second	25				
Power Pack		380 v 50 HZ, AC 0.75 kw				
Net Weight	kg	357	364	326	332	352

SPECIFICATION IS SUBJECT TO CHANGE WITHOUT NOTICE

Low Profile Lift Table HY 1500 Kg , HY 2000 Kg

- ▲ Heavy duty design with larger platform
- ▲ These tables achieve a low closed height, eliminating the need for a pit installation.
- ▲ They are manufactured to all European safety standards including EN1570:1999.
- ▲ Remote power pack with pedestal and controls, protected to IP54.
- ▲ Upper platform fitted with safety perimeter to prevent descent on contact with obstructions.
- ▲ 24V control box with UP and DOWN buttons and emergency stop.
- ▲ External power pack equipped with a relief valve against overloading and a compensated flow valve for controlling lowering speed. Power supply are AC 380V/50HZ/3phase.
- ▲ Hose burst safety valve to stop the lift table lowering in case of hose breakage.
- ▲ Removable lifting eyes to facilitate handling and installation of the lift table.
- ▲ Oilless bushings on pivot points.
- ▲ Loading ramp is a standard equipment.



รายละเอียดผลิตภัณฑ์อาจมีการเปลี่ยนแปลงโดยมิได้แจ้งให้ทราบล่วงหน้า

TECHNICAL DATA		MODEL				
		HY 1501	HY 1502	HY 1503	HY 2001	HY 2002
Capacity	kg	1500			2000	
Platform Width	mm	800	1000	1200	1200	1000
Platform Length	mm	1600	1600	1600	1600	1600
Hydraulic Cylinder	set	2				
Lifting Height	mm	870				
Lowering Height	mm	105				
Stroke	mm	775				
Lift Time	second	30				
Power Pack		380 v 50 HZ,AC 1.5 kw			380 v 50 HZ,AC 2.2 kw	
Net Weight	kg	367	401	415	419	405

SPECIFICATION IS SUBJECT TO CHANGE WITHOUT NOTICE