

## Electric Pallet Truck WP 10 - 20



รายละเอียดผลิตภัณฑ์อาจมีการเปลี่ยนแปลงโดยมิได้แจ้งให้ทราบล่วงหน้า

# Electric Pallet Truck 2.0t

รายละเอียดผลิตภัณฑ์อาจมีการเปลี่ยนแปลงโดยมิได้แจ้งให้ทราบล่วงหน้า

Characteristics			
1.1	Manufacturer		PE
1.2	Model designation		WP 10-20
1.3	Drive unit		Battery
1.4	Operator type		Walkie
1.5	Load capacity	Q (kg)	2000
1.6	Load center	c (mm)	600
1.8	Load distance (Raised/ Lowered)	x (mm)	874/ 965
1.9	Wheelbase	y (mm)	1454
1474			
Weights			
2.1	Service weight (Incl. battery)	kg	610
2.2	Axle loading, laden operator/load side	kg	870/ 1740
2.3	Axle loading, unladen operator/load side	kg	458/ 152
Wheels, Chassis			
3.1	Tyre type		PU/ PU
3.2	Tyre size, operator side		Φ266X126
3.3	Tyre size, load side		Φ80x120, Φ80X80
3.4	Balance wheels (dimensions)		Φ85x50
3.5	Wheels, number operator/load side (x=drive wheels)		1x+ 2/ 4
Dimensions			
4.4	Lift height	$h_3$ (mm)	120
4.9	Height of tiller arm in operating position, min/ max	$h_{14}$ (mm)	1280, 1190/ 770
4.15	Fork height, lowered	$h_{13}$ (mm)	85
4.19	Overall length	$l_1$ (mm)	1802
1852			
4.20	Length to face of forks	$l_2$ (mm)	780
4.21	Overall width	$b_1/ b_2$ (mm)	764
4.22	Fork dimensions	s/ e/ l (mm)	55/ 185/ 1150
55/ 185/ 1200			
4.25	Fork spread, min/ max	$b_5$ (mm)	540/ 685
4.32	Ground clearance, center of wheelbase	$m_2$ (mm)	35
4.33	Aisle width, 1000x1200 pallet crossways	Ast (mm)	1912
4.34	Aisle width, 800x1200 pallet lengthways	Ast (mm)	2102
4.35	Outer turning radius	Wa (mm)	1667
1688			
Performance			
5.1	Travel speed, laden/ unladen	km/ h	4.6/ 5.9
5.2	Lifting speed, laden/ unladen	m/ s	0.051/ 0.06
5.3	Lowering speed, laden/ unladen	m/ s	0.052/ 0.059
5.8	Maximum gradeability, laden/ unladen $S_2$ 5 min.	%	5/ 7
5.10	Service brake		Mechanical
Drive			
6.1	Drive motor rating $S_2$ 60 min.	kW	0.93
6.2	Lift motor rating at $S_3$ 15%	kW	2.2
6.4	Battery voltage/ rated capacity (5h)	V/ Ah	24/ 210
6.5	Battery weight	kg	220
	Battery compartment dimensions l/ w/ h	mm	740x220x560
	Battery type		Industry battery
Others			
8.1	Type of drive control		DC
	Manufacturer		CURTIS
8.4	Sound level at operator's ear	dB (A)	70

