

A]b]a cj Yf '9 `Ywf]WDU`Yh]fi W `K D` %!'`%*



รายละเอียดผลิตภัณฑ์อาจมีการเปลี่ยนแปลงโดยมิได้แจ้งให้ทราบล่วงหน้า

Minimover Electric Pallet Truck 1.3t

รายละเอียดผลิตภัณฑ์อาจมีการเปลี่ยนแปลงโดยมิได้แจ้งให้ทราบล่วงหน้า

Characteristics			
1.1	Manufacturer		EP
1.2	Model designation		WP61-13
1.3	Drive unit		Battery
1.4	Operator type		Walkie
1.5	Load capacity	Q (kg)	1300
1.6	Load center	c (mm)	600
1.9	Wheelbase	y (mm)	1234
Wheels, Chassis			
3.1	Tyre type		PU/ PU
3.2	Tyre size, operator side		Φ252X67
3.3	Tyre size, load side		Φ73x98 (single), Φ80X58(double)
3.4	Balance wheels (dimensions)		Φ99.5x40
3.5	Wheels, number operator/ load side (x=drive wheels)		1x+ 2/ 2
Dimensions			
4.9	Height of tiller arm in operating position, min/ max	h_{14} (mm)	777/ 1200
4.15	Fork height, lowered	h_{13} (mm)	74/ 85
4.19	Overall length	l_1 (mm)	630
4.20	Length to face of forks	l_2 (mm)	500
4.21	Overall width	b_1/ b_2 (mm)	724
4.22	Fork dimensions	$s/ e/ l$ (mm)	44/ 160/ 1150 or 1200
4.25	Fork spread, min/ max	b_5 (mm)	540/ 685
4.32	Ground clearance, center of wheelbase	m_2 (mm)	40
4.33	Aisle width, 1000x1200 pallet crossways	A_{st} (mm)	1720
4.34	Aisle width, 800x1200 pallet lengthways	A_{st} (mm)	1540
4.35	Outer turning radius	W_a (mm)	1400
Performance			
5.1	Travel speed, laden/ unladen	km/ h	3.5/ 4
5.2	Lifting speed, laden/ unladen	m/ s	0.056/ 0.06
5.3	Lowering speed, laden/ unladen	m/ s	0.057/ 0.059
5.8	Maximum gradeability, laden/ unladen S_2 5 min.	%	5/ 7
5.10	Service brake		Electromagnetic
Drive			
6.1	Drive motor rating S_2 60 min.	kW	0.6
6.2	Lift motor rating at S_3 15%	kW	0.8
6.4	Battery voltage/ rated capacity (5h)	V/ Ah	24/ 70
6.5	Battery weight	kg	66
	Battery compartment dimensions l/ w/ h	mm	—
	Battery type		Maintenance free battery
Others			
8.1	Type of drive control		DC
	Manufacturer		CURTIS
8.4	Sound level at operator's ear	dB (A)	70

