

Electric Reach Stacker ***EQ 1200 EQ 1500***



รายละเอียดผลิตภัณฑ์อาจมีการเปลี่ยนแปลงโดยมิได้แจ้งให้ทราบล่วงหน้า

Electric Reach Stacker

รายละเอียดผลิตภัณฑ์อาจมีการเปลี่ยนแปลงโดยมิได้แจ้งให้ทราบล่วงหน้า

TECHNICAL DATA		MODEL							
		EQ 1216	EQ 1225	EQ 1233	EQ 1245	EQ 1516	EQ 1525	EQ 1533	EQ 1545
Power		battery							
Load capacity	kg	1200				1500			
Lift height	H1 mm	1600	2500	3300	4500	1600	2500	3300	4500
Load centre	Q mm	500							
Fork carriage tilt (forward / backward)	α / β (deg)	2 / 4							
Travel speed (with / without load)	km / h	4.5 / 5.5							
Lifting speed (with / without load)	mm / s	90 / 125							
Max gradeability (with / without load)	%	6 / 8							
Wheel base	Y mm	1350							
Service brake		Electromagnetic							
Overall length	L mm	2300							
Overall width	mm	1100							
Height of mast,lowered	H2 mm	1985	1785	2185	2140	1985	1785	2185	2140
Height of mast,extended	H3 mm	2235	3260	4060	5400	2235	3260	4060	5400
Free lift height	h4 mm		-		1530		-		1530
Reach distance	X1 mm	550							
Fork dimensions	mm	35 x 100 x 1070				40 x 100 x 1070			
Min turning radius	wa mm	1500							
Service weight	kg	1350	1480	1580	1780	1550	1680	1780	1980
Drive motor	kw	1.2			1.5				
Lift motor	kw	2.5	3						
Battery (5 h)	V / Ah	24 / 240			24 / 270				
Tyres		polyurethane							
Size of front tyre	mm	178 x 75							
Size of rear tyre	mm	250 x 80			230 x 76				
Size of balancing tyre	mm	156 x 75							
Speed control system		CURTIS / CurTis DC							

SPECIFICATION IS SUBJECT TO CHANGE WITHOUT NOTICE